

## FUSO FJ



DIMENSIONS & WEIGHT		FJ 2528C	FJ 2528R
Overall Length / Width / Height	(mm)	7,160 / 2,490 / 2,962	11,967 / 2,490 / 2,905
Wheelbase	(mm)	4,275	6,375
Wheel Tread (Front / Rear)	(mm)	2,045 / 1,805	
Cab to Rear Axle (CA)	(mm)	4,570	6,670
Cab to End Frame (CE)	(mm)	5,320	10,127
Frame Width	(mm)	762	758
Curb Weight	(kg)	8,284	7,678
Payload	(kg)	16,700	17,322
GVW	(kg)	25,000	



ENGINE & TRANSMISSION		FJ 2528C	FJ 2528R
Model		6S20	
Type		4-Stroke Direct Injection Diesel with Turbocharger	
Cylinders		In-line 6	
Displacement	(cc)	6,374	
Bore x Stroke	(mm)	102 x 130	
Max. Power	(Ps / rpm)	285 / 2,200	
Max. Torque	(N-m / rpm)	1,120 / 1,200 - 1,600	
Fuel Tank Capacity	(L)	290	380
AdBlue Tank Capacity	(L)	60	
Transmission (Type)		9 Forward and 1 Reverse M/T (Synchromesh)	
P.T.O. Type		Spline	Flange



AXLE		FJ 2528C	FJ 2528R
Front / Rear		Reverse Elliot / Fully Floating	
<b>SUSPENSION</b>			
Front		Parabolic Leaf Spring with Shock Absorber and Anti-Roll Bar	
Rear		Tandem Bogie with Anti-Roll Bar	Semi-Elliptic Balancer Type with Anti-Roll Bar



BRAKE		FJ 2528C	FJ 2528R
Service		Fully Air S-Cam, Dual Circuit	
Parking		Pneumatically Operated Spring Actuator with Hand Brake Valve Acting on Rear Axle	
Auxiliary		Engine and Exhaust	
<b>TIRE &amp; WHEEL</b>			
Tire (Front / Rear)		Radial 11.00 R20	Tubeless 295 / 80 R22.5
Wheel		7.5 x 20	8.25 x 22.5
<b>STEERING</b>			
Gear Type		Hydraulic Power Assisted	
Power Steering		Equipped	
Steering Wheel Adjust		Tilt and Telescopic	
<b>SAFETY</b>			
		3 pt. ELR x2 and 2 pt. Lapbelt (Center), Collapsible Steering Wheel, Side Impact Beams, and Anti-Lock Braking System (ABS)	

Photos and specifications may vary from actual unit. Sojitz Fuso Philippines reserves the right to change specifications without prior notice.



FUSO authorized distributor  
**SOJITZ FUSO PHILIPPINES CORPORATION**  
[www.fuso.com.ph](http://www.fuso.com.ph)

Brochure part no.: H010101



SOJITZ FUSO PHILIPPINES CORPORATION



**FJ 2528C** • Short wheelbase • 8.1m Min. Turning Radius • Equipped with Spline type P.T.O.  
(Dump optional rear body)



**FJ 2528R** • Natural 32 ft. Loading Span • Equipped with Flange type P.T.O. (Wing Van optional rear body)



The multi-adjustable air pressure driver's seat and tilt and telescopic adjustable steering wheel allow the driver to set the optimum driving position.



The cruise control further lends a fatigue-free drive while the power windows adds convenience



The FJ's aerodynamic cab design reduces wind resistance thus reducing cabin noise while increasing fuel efficiency



Daytime Running Lights (DRL)



The intelligent meter cluster provides all the necessary information




The frame is shot-peened and powder coated to prevent corrosion and increase durability. Higher flange width and web height also offer stability and load bearing ability leading to longer frame life while the alligator type cross members make it exceptionally strong.



The direct injection diesel engine combines high output and flat torque for power hungry applications



The Fuso FJ is equipped with Anti-Lock Braking System (ABS)



The Differential Lock Buzzer informs driver of differential lock position



The Fuso FJ is equipped with a smooth-shifting 9-speed manual transmission which provides a higher flexibility of gear selection for various operating conditions thereby enhancing driving performance and improving fuel efficiency