



PUV

FUSO CANTER MODERN PUV

DIMENSIONS & WEIGHT		CLASS II PUV TILT	CLASS III PUV TILT	CLASS II PUV UNIBODY	CLASS III PUV UNIBODY
Overall Length / Width / Height	(mm)	6,060 / 1,820 / 2,800	6,405 / 1,120 / 2,800	6,090 / 1,820 / 2,585	6,430 / 1,820 / 2,585
Wheelbase	(mm)	3,400	3,400	3,400	3,400
Seating Capacity		19 + 1	23 + 1	19 + 1	23 + 1
Standing Capacity		10	Not Applicable	10	Not Applicable
Gross Vehicle Weight (GVW)	(kg)	4,490	4,490	4,490	4,490
SAFETY					
Seat belts		Partially Equipped	Partially Equipped	Partially Equipped	Partially Equipped
Collapsible Steering Wheel		Equipped	Equipped	Equipped	Equipped
R.I.S.E. (Reinforced Impact Safety Evolution)		Equipped	Equipped	Equipped	Equipped
Dashcam and Reverse Cameras		Equipped	Equipped	Equipped	Equipped
Anti-Lock Braking System (ABS)		Equipped	Equipped	Equipped	Equipped
Electronic Brakeforce Distribution (EBD)		Equipped	Equipped	Equipped	Equipped
COMFORT					
CCTV Cameras		Equipped	Equipped	Equipped	Equipped
Passenger Cabin TV		Equipped	Equipped	Equipped	Equipped
Automatic Rear Passenger Door		Equipped	Equipped	Equipped	Equipped
Air Condition		Equipped	Equipped	Equipped	Equipped
LED Route Signage		Equipped	Equipped	Equipped	Equipped
ENGINE					
Model		4P10-WAT2	4P10-WAT2	4P10-WAT2	4P10-WAT2
Type		Turbo-Intercooler, DOHC, Common-Rail Direct Injection, Diesel Engine			
Cylinders		4 In-line	4 In-line	4 In-line	4 In-line
Displacement	(cc)	2,998	2,998	2,998	2,998
Max. Power	(Ps / rpm)	131 / 2,620	131 / 2,620	131 / 2,620	131 / 2,620
Max. Torque	(N-m / rpm)	350 / 1,400	350 / 1,400	350 / 1,400	350 / 1,400
Fuel Tank Capacity	(L)	100	100	100	100
TRANSMISSION					
Type		5 Forward, 1 Reverse M/T (Synchromesh Type)			
AXLE					
Front		Reverse Elliot "I" Beam			
Rear		Fully Floating			
SUSPENSION					
Front and Rear		Laminated Leaf Springs			
Shock Absorber (Front and Rear)		Hydraulic Double Acting Telescopic			
BRAKE					
Service		Disk Brake - Dual Circuit			
Parking		Internal Expanding Type on Propeller Shaft			
Auxiliary		Exhaust Brake			
TIRE & WHEEL					
Tire	Front / Rear	(Tubeless) Single 205/75R16 / Dual 205/75R16			
Wheel		16 x 5 1/2K-115-8t, 5 studs			
STEERING					
Gear Type		Ball and Nut Type with Integral Type Hydraulic Power Booster			
Power Steering		Equipped			
Steering Wheel Adjust		Tilt and Telescopic with Steering Lock			
ELECTRICAL SYSTEM					
Electrical System		12V x2 (Parallel)			
Battery		115D31L			
Alternator		140 amperes			

Photos and specifications may vary from actual unit. Sojitz Fuso Philippines reserves the right to change specifications without prior notice.



MITSUBISHI FUSO Authorised Distributor
SOJITZ FUSO PHILIPPINES CORPORATION
www.fuso.com.ph

CANTER COMMUTE

CANTER EXPRESS

Actual unit may vary from photos shown.



Mas stable ang biyahe dahil sa dual rear wheels



Mas madali ang maintenance dahil sa cab tilting feature (sa FUSO Canter lang!)

Matipid, malakas, at maaasahang 4 In-line cylinder, common-rail direct injection, turbo-intercooler, diesel engine (4P10-WAT2 Euro 5-compliant)



Tatlong maluluwag na compartment para sa maginhawa at mas ligtas na biyahe ng mga pasahero.

Body builders: **ALMAZORA** Motors Corporation **CENTRO** MANUFACTURING CORPORATION



All-around safety. Equipped with front dashcam, rear camera, and front and passenger cabin CCTV cameras.

CANTER EXPRESS

Maluwag na passenger cabin with front-facing seats and seatbelts para sa 23 na pasahero



Automatic rear passenger door para sa mas madaling pagsakay at pagbaba ng mga pasahero



Air-conditioner made for Philippine weather para kumportable ang mga pasahero



Passenger cabin TV



CANTER COMMUTE

Maluwag na passenger cabin para sa 30 na pasahero



PNS-compliant LED signage para sa mas madaling mabasa na ruta

Kumportableng pagmamaneho ang hatid ng FUSO Canter; reclining seats, maluwag na legroom, tilt & telescopic steering wheel, at dash-mounted gear shifter para mas hindi pagod sa biyahe!

